

FEATURES 設備特性

1. Melting tank, dispensing nozzle and hose could be heated orderly to avoid the nozzle over heat and to reduce the carbonization.
熔膠槽與保溫管、噴槍順序加熱，避免保溫管、噴槍加熱時間過長，減少膠質碳化、節省用電。
2. Weekly timer for setting the time to turn on and off the machine automatically by requirements.
全週預約開關機功能，可依實際功能需求設定每天不同的開關機時間。
3. The function of keep warm as a "Stand-By" status to reduce the carbonized of the hot melt and meet the envelopment friendly purpose.
停機保溫功能，減少膠質碳化符合環保節能需求。
4. The function of warning malfunction.
故障警報警示功能。
5. The gear pump is install vertically for stable the glue pumping rate and easy for maintenance.
齒輪泵浦獨立懸吊系統，出膠穩定，保養、維修省時方便。
6. With a precision glue flow adjustor valve and electrical inverter for the motor to ensure the glue flow satiability.
精密流量調節開關，搭配電子式變頻器，可使出膠量調整精確。
7. Double layer stainless steel filter net to catch the impurities for extend the machine life.
雙層不鏽鋼過濾網，有效過濾雜質，延長機器使用壽命。
8. Individual temperature control with digital controller for melting tank, dispensing nozzle and hose.
全數位顯示功能，熔膠槽、噴頭與保溫管獨立控溫顯示。



SPECIFICATIONS 設備規格

SPEC 規格	UNIT 單位	HS110C2
Tank Capacity 膠槽容量	Liter	10
Max. Melting Rate 最大熔膠速率	Kg/HR	10
Max. Operation Temp. 最高操作溫度	°C	200
Viscosity 使用黏稠度	CPS	30000
Available Hose/Gun 保溫管/噴槍數目	Set	1 - 2
Max. Glue Flow Rate 最大出膠速率	g/MIN	400
Dimensions (L×W×H) 尺寸 (長×寬×高)	mm	700×430×470
Weight 重量	Kg	Approx. 65
Machine Power Rate 主機功率	Watt	3420
Adapter Power Rate 配件功率	Watt	Hose 保溫管約: 3/8": 160Watt/meter 5/8": 220Watt/meter Gun 手提噴槍約: 100 Watt Nozzle 噴頭約: 240 Watt
Power Requirement 電力需求		220V AC, 16A, 50/60Hz, 1Ø

* The flow rate depends on the viscosity of hot melt adhesive. 實際出膠量會依熱熔膠的黏稠度改變

* Total power consumption and electricity requirement depends on the adapter demand. 總功率與電力需求會依配件需求變動

HWANG SUN ENTERPRISE CO., LTD. 皇尚企業股份有限公司

www.hes.com.tw | hwangsun@seed.net.tw

Headquarters 臺灣總公司

No.15, Xinhe 2nd Rd.,
South District, Tainan 70248, Taiwan
70248 台南市安平工業區新和二路15號
TEL: +886-6-2644191 FAX: +886-6-2644743

Dongguan Hwang Sun Industrial Co., Ltd.
東莞皇尚實業有限公司

Guangchang Road, Tingshan Village, Houjie Town,
Dongguan, Guangdong, 523943, China
中國廣東省東莞市厚街鎮汀山村廣場路
TEL: +86-769-81636099 FAX: +86-769-81636399

Taichung 台中營業所

4F-4, No. 82, Daying W. 1st St.,
Nantun District, Taichung 40865, Taiwan
40865 台中市南屯區大英西一街 82 號 4 樓之 4
TEL: +886-4-24739593 FAX: +886-4-24714414

Kunshan 昆山

Room 902, Building 7, No.495 Yangshu Road,
Kunshan City, Suzhou City, 215334, China
江蘇省昆山市玉山鎮開發區楊樹路495號玫瑰灣7號
樓902室
TEL: +86-18862117147

Taipei 台北營業所

1F, No. 25-1, Hami St.,
Datong District, Taipei 10370, Taiwan
10370 台北市哈密街 25 之 1 號 1 樓
TEL: +886-2-25933744 FAX: +886-2-25933745